

Power Quality Solutions

# Eaton 93E UPS

15 - 500 kVA

Simply effective power management  
for every critical environment



**EATON**

*Powering Business Worldwide*

# The Eaton 93E: simply effective

The Eaton 93E UPS delivers **simply effective** power protection for ever-expanding loads in today's space-constrained data centres. Facilitating a lower total cost of ownership (TCO) through a combination of energy-efficiency, high reliability and a compact footprint the 93E is an ideal solution for small - to medium - sized data centres and other applications desiring highly reliable power protection.

## Energy-efficient design

With a transformer-free design and sophisticated sensing and control circuitry the 93E is capable of achieving up to a 99% efficiency rating, making it one of the most energy-efficient UPSs in its class - and it still provides maximum load protection. Unlike most high efficiency UPSs, the 93E:

- Provides surge suppression for the load
- Detects the location of faults (utility or load) and takes the appropriate action
- Switches to double-conversion operation in less than 4ms

High system efficiency reduces utility cost, extends battery run times and ensures cooler operating conditions.

## Real compatibility

Active power factor correction (PFC) provides 0.99 input power factor and <5% ITHD, thus eliminating interference with other critical equipment in the same network and enhancing compatibility with generators. The 93E is optimised for protecting modern 0.9 p.f. rated IT equipment without the need to oversize.



## Application

- Small and Medium data centres
- Industrial automation equipment
- Telecommunications
- Healthcare



**300/400/500 kVA**

## True reliability

Patented Powerware Hot Sync® technology makes it possible to parallel up to four UPSs to increase availability or add capacity.

The technology enables load sharing without any communication line, thus eliminating single point of failure.

## Compact & serviceable design

Small footprint occupies minimal floor space:

- Up to 60% smaller than similar competitive solutions
- Allows dedication of more floor space to revenue producing equipment

The 93E is easily and quickly serviced to provide the highest level of availability with Mean Time to Repair (MTTR) <30 minutes. With its Easy Capacity Test feature the 93E can test its entire power train under full load stress without the requirement of an external load.

## Flexible installation options

Eaton's range of accessories for the 93E provides flexible installation options that expedite deployment and save valuable space. The aesthetically designed accessories enable coordinated solutions that enhance both safety and reliability whilst reducing installation time and total cost.

The accessories family includes System Parallel Modules, External Maintenance Bypass Switches, External Battery Cabinets, External Battery Circuit Breakers, Top cable Entry Cabinets, Rear Chimneys, IP21 kit (15-200kVA) & Internal Transformer Options (15-100kVA).

## User Interface

Large LCD graphically displays UPS status and offers easy access to measurements, controls and settings.



## Connectivity

With Eaton® Mini-Slot connectivity cards, you can monitor, manage and remotely shutdown UPSs across the network.

- Network Card-MS Web/SNMP Card allows you to connect your 93E UPS directly to the Ethernet network and the Internet
- Network and MODBUS Card-MS provides remote monitoring of a UPS system through a Building Management System (BMS) or Industrial Automation System (IAS)
- Relay Card-MS provides the essential dry-contact interface between your Eaton UPS and any relay-connected computer as well as a variety of industrial applications



## Software

Eaton's Intelligent Power® Software Suite incorporates two important applications for ensuring quality power and uptime: monitoring and management of power devices across the network combined with automatic, graceful shutdown when faced with an extended power outage.

- Monitor and manage multiple power devices across your network
- Extend the uptime of dual-powered servers with redundancy capabilities
- Enable server shutdown and live migration events



## Eaton's heritage in industry-leading UPS design and production

For more than 50 years, Eaton has been safeguarding the critical systems of businesses across the globe. Whether protecting a single desktop or the largest data centre, Eaton solutions provide clean, uninterrupted power to keep mission-critical applications working.

We offer a comprehensive range of environmentally-sensitive, efficient, reliable UPSs, surge protective devices, power distribution units (PDUs), remote monitoring, meters, software, connectivity, enclosures, airflow management and professional services.

We work with IT and facilities managers to effectively manage power in virtually every business segment, including data centres, retail outlets, health-care organisations, governmental agencies, manufacturing firms, broadcasting companies, financial institutions, and a wide variety of other applications.

Our solutions provide the power to make a difference, helping you achieve your business goals while maintaining environmentally sustainable enterprises.

### A world-class support structure

As an industry-leading UPS provider, at Eaton we're constantly working to ensure that our service standards meet your needs precisely. Our trained service team is on hand 24/7 to minimise risks by detecting and addressing problems before they happen. In the Asia Pacific region Eaton's service network consists of

more than 200 field engineers who receive comprehensive, up-to-date training on the latest products and technologies.

We confidently guarantee the experience and know-how of our servicing resources to provide a dedicated support package which helps to ensure your equipment is running safely, reliably, sustainably and energy-efficiently at all times.



# Eaton 93E UPS Technical Specifications

| Power                            |   |   |
|----------------------------------|---|---|
| Ratings                          | 15kVA/13.5kW<br>30kVA/27kW<br>60kVA/54kW<br>100kVA/90kW<br>160kVA/144kW<br>300kVA/270kW<br>500kVA/450kW   | 20kVA/18kW<br>40kVA/36kW<br>80kVA/72kW<br>120kVA/108kW<br>200kVA/180kW<br>400kVA/360kW  |
| Topology                         | Double-conversion online UPS  |   |
| Operating frequency              | 50/60 Hz (40 to 72 Hz)  |   |
| Input power factor               | >0.99 typical   |   |
| Input current distortion         | ≤5% THD   |   |
| Electrical input                 |   |   |
| Nominal input voltage            | 400/230V, 4 wire (380/415V selectable)  |   |
| Input voltage range              | -15%, +20% from nominal (400V) at 100% load without depleting battery   |   |
| Electrical output                |   |   |
| Nominal output voltage           | 400/230, 4 wire (380/415V selectable)   |   |
| Output voltage regulation        | ±1% Static; <5% dynamic at 100% resistive load change, <20 ms response time   |   |
| Battery                          |   |   |
| Battery                          | 192 to 240 Cells (Continual selectable for 15-80kVA)<br>216/222/228/234/240 Cells (Selectable for 100-500kVA)   |   |
| Charging method                  | ABM Cyclic Charging   |   |
| General                          |   |   |
| Efficiency                       | >98% High-efficiency mode (15-80kVA)<br>>98.5% High-efficiency mode (100-300kVA)<br>>99% High-efficiency mode (400-500kVA)<br>>94% Double conversion mode (15-300kVA)<br>>96% Double conversion mode (400-500kVA) |   |
| Overload                         | 150% for 1 minute, 125% for 10 minutes,<br>>150% for 150ms  |   |
| UPS bypass                       | Automatic on overload or UPS failure  |   |
| Parallel technology              | Powerware Hot Sync® Technology  |   |
| Dimensions W x D x H (mm)        | 500 x 710 x 960<br>500 x 710 x 1230<br>500 x 710 x 1500<br>600 x 800 x 1876<br>1600 x 820 x 1880  | 15-20kVA (with internal battery)<br>30kVA (with internal battery)<br>40kVA (with internal battery)<br>60-200kVA<br>300/400/500kVA |
| Cabinet rating                   | IP20 with standard washable dust filters  |   |
| Weights without internal battery | 72kg<br>88kg<br>120kg<br>202kg<br>245kg<br>283kg<br>311kg<br>457kg<br>860kg<br>970kg<br>1020kg  | 15/20kVA<br>30kVA<br>40kVA<br>60kVA<br>80kVA<br>100kVA<br>120kVA<br>160/200kVA<br>300kVA<br>400kVA<br>500kVA                      |
| Weights with internal battery    | 272kg<br>376kg<br>490kg   | 15/20kVA<br>30kVA<br>40kVA  |

| Communications   |  |
|--|--|
| Display  | Graphical LCD with blue backlight  |
| LEDs   | (4) LEDs for notice and alarm  |
| Audible alarms   | Yes  |
| Communication ports  | (1) RS-232, (1) USB, (1) EPO   |
| Communication slots  | (2) Mini-slot communication bays   |
| Environmental  |  |
| Operating temperature  | 0°C to +40°C<br>Batteries recommended max. +25°C   |
| Storage temperature  | -25°C to +55°C without batteries<br>+15°C to +25°C with batteries  |
| Relative humidity  | 5-95%, non-condensing  |
| Audible noise  | 15-20kVA≤55 dBA at 1m typical<br>30-40kVA≤62 dBA at 1m typical<br>60-120kVA≤65 dBA at 1m typical<br>160-200kVA≤70 dBA at 1m typical<br>300-400kVA≤73 dBA at 1m typical<br>500kVA≤75dBA at 1m typical |
| Altitude   | <1000m at +40°C  |
| Certifications   |  |
| EMI standards  | EN55022/EN55024  |
| EMC compliance   | IEC 62040-2  |
| Quality  | ISO 9001: 2000 and ISO 14001:1996  |
| Communication accessories  |  |
| Network-MS   | Web/SNMP Card  |
| Modbus-MS  | Web/SNMP and Modbus Card   |
| Relay-MS   | Relay (Dry Contact) Card -DB9 Connection   |
| Industrial Relay   | Relay (Dry Contact) Card -Terminal Connection  |
| 116750224-001  | Environmental Monitor Probe (EMP) kit (need to plug into Web/SNMP Card or Web/SNMP and Modbus Card to work)  |
| System accessories   |  |
| Battery cabinets & battery circuit breakers (60-200kVA)              |  |
| Maintenance Bypass Switches (MBS) (100-200kVA, standard on 15-80kVA) |  |
| Top cable entry (60-200kVA, standard on 300-500kVA)                  |  |
| System parallel modules (60-200kVA)                                  |  |
| Dual input kit (15-80kVA)  |  |
| IP21 hood (15-200kVA)  |  |
| Rear chimney (60-200kVA)   |  |

Due to continuous product improvements, specifications are subject to change without notice.

For more information visit: [eaton.com/93E](http://eaton.com/93E)

## SINGAPORE

T +65 6825 1684  
E EatonSEA@eaton.com

## HONG KONG

T + 852 2830 3077  
E EE-Marketing-HK@eaton.com

## KOREA

T + 82 2 6238 7949  
E EatonKoreaES@eaton.com

## MALAYSIA

T + 603 7804 3618  
E EatonSEA@eaton.com

## VIETNAM

HANOI  
T + 84 4 393 65 303  
E EatonSEA@eaton.com

## PHILLIPINES

T + 63 (2) 812 3045  
E EatonSEA@eaton.com

## INDONESIA

T + 62 21 29499 000  
E EatonSEA@eaton.com

## HCMC

T + 84 86255 6737  
E EatonSEA@eaton.com

## THAILAND

T + 66 (0) 2511 5300  
E EatonSEA@eaton.com

Sales enquiries for Bangladesh, Cambodia, Myanmar and Laos, please contact our Thailand office.

Eaton is a trade name, trademark and/or service mark of Eaton Corporation or its subsidiaries and affiliates.